

IMO Safety Signs

SKU - 40021057

Person Overboard Call Point



DESCRIPTION

Eco-friendly photoluminescent safety signs for person overboard call point – fully compliant with IMO and ISO regulations. Crafted using sustainable PETX material, offering easy installation with self-stick PE closed-cell foam backing. Complete with reference codes and article numbers for clear identification. Rescue signs are critical components of a safety sign system, playing a pivotal role in ensuring swift and safe evacuation during emergencies in maritime environments, offshore installations, or buildings. Serving as crucial markers, rescue signs guide individuals to safety by providing clear direction and vital information.

KEY FEATURES

- Halogen and PVC Free: Crafted with modern, safe, and eco-friendly materials.
- 100% Environmentally Friendly and Recyclable: Committed to reducing our carbon footprint with recyclable materials for a greener future.
- Back Printed for Durability: Features a back-printed design for added protection, ensuring long-lasting performance and resistance to fading.
- Glossy, Quality Finish, Easy to Wipe Clean: Glossy finish for easy maintenance, saving time and effort. Professional look.
- Easy to Mount with Self-Adhesive Backing: User-friendly self-adhesive backing for quick and hassle-free installation.
- 5-Year Warranty, Even on Outdoor Use: Provided with a 5-year warranty, demonstrating enhanced reliability and confidence in performance, including outdoor applications. Enhanced reliability and confidence in the performance of the signs, backed by an extended warranty period.

1





IMO Safety Signs

SKU - 40021057

Person Overboard Call Point

SPECIFICATION

- Material: Halogen and PVC Free PET-X XL
- Environmental Friendly: 100% recyclable, contributing to a greener future
- Durability: Back printed design for extra protection against wear and tear
- Finish: Glossy, quality finish, easy to wipe clean
- Installation: Self-adhesive backing for easy mounting
- Warranty: 5-year warranty, even for outdoor use
- Available Sizes: 150x150mm
- Compliance: Fire-retardant and in accordance with IMO Res. A760 (18) as amended ISO 17631:2002
- Recommended height for installation: Approximately 160cm from the floor level
- PETX Sign XL Glow: 10 min / 75mcd/m² - 60 min / 10 mcd/m², decay time: 1250 min

Article Codes:

ISSA:

IMPA:

TECHNICAL INFORMATION

- Fire-retardant, Halogen and PVC Free Safety Signs
- All Safety Signs Corresponding to IMO Res. A760 (18) as amended ISO 17631:2002
- Green Passport
- DNV Wheelmark certificate module B & D
- Texts and symbols comply with international standards
- HS Code: 39199000.99

2

www.icbrindle.com

+44 (0) 1202 657814

info@icbrindle.com

Follow us on :

