



Marine &amp; Offshore

Certificate number: 23131/D0 BV

File number: ACM 136/2103/01

Product code: 2180H

*This certificate is not valid when presented without the full attached schedule composed of 7 sections*

[www.veristar.com](http://www.veristar.com)

## TYPE APPROVAL CERTIFICATE

*This certificate is issued to*

**T-ISS B.V.**

Zoetermeer - NETHERLANDS

*for the type of product*

**ANTI-SPRAYING PIPE FLANGES & JOINTS SYSTEMS**

SPRAYSTOP Standard and SPRAYSTOP 50 Plus anti-splash tapes

### Requirements:

- BUREAU VERITAS Rules for the Classification of Steel Ships
- SOLAS 74 as amended, Regulation II-2/4.2.2.5.3 /4.2.3 /4.2.4

*This certificate is issued to attest that Bureau Veritas Marine & Offshore did undertake the relevant approval procedures for the product identified above which was found to comply with the relevant requirements mentioned above.*

*This certificate is a renewal of certificate N° 23131/C0 BV expiring on 05/03/2025*

**This certificate will expire on: 05 Mar 2030**

**For Bureau Veritas Marine & Offshore,**

At BV GRONINGEN, on 18 Feb 2025,

Olaf RUITER

***This certificate was created electronically and is valid without signature***



This certificate remains valid until the date stated above, unless cancelled or revoked, provided the conditions indicated in the subsequent page(s) are complied with and the product remains satisfactory in service. This certificate will not be valid if the applicant makes any changes or modifications to the approved product, which have not been notified to, and agreed in writing with Bureau Veritas Marine & Offshore. Should the specified regulations or standards be amended during the validity of this certificate, the product(s) is/are to be re-approved prior to it/they being placed on board vessels to which the amended regulations or standards apply. This certificate is issued within the scope of the General Conditions of Bureau Veritas Marine & Offshore available on the internet site [www.veristar.com](http://www.veristar.com). Any Person not a party to the contract pursuant to which this document is delivered may not assert a claim against Bureau Veritas Marine & Offshore for any liability arising out of errors or omissions which may be contained in said document, or for errors of judgement, fault or negligence committed by personnel of the Society or of its Agents in establishment or issuance of this document, and in connection with any activities for which it may provide.

The electronic version is available at: <https://www.veristarm.com/veristarnb/jsp/viewPublicPdfTypepec.jsp?id=jwm06ut0vi>

BV Mod. Ad.E 530 June 2017

This certificate consists of 3 page(s)

## **THE SCHEDULE OF APPROVAL**

### **1. PRODUCT DESCRIPTION**

#### **SPRAYSTOP Standard and SPRAYSTOP 50 Plus anti-splash tapes**

##### **Design Specification**

Size	Thickness (mm)	Width (mm)	Length (m)
Spray Stop standard	$0.21 \pm 0.017$	35 to 1000	10
Spray Stop 50 Plus	$0.33 \pm 0.02$	35 to 1000	10

	Total thickness Spray stop standard (mm)	Total thickness Spray stop 50 Plus (mm)
Al-glass fiber	$0.110 \pm 0.01$	$0.210 \pm 0.01$
Glue	$0.050 \pm 0.005$	$0.070 \pm 0.005$
PET Liner	$0.050 \pm 0.002$	$0.050 \pm 0.002$

	SPRAYSTOP	SPRAYSTOP 50 Plus
Maximum pressure (bar)	21	50 (with minimum two layers)
Maximum fluid temperature (°C)	150	150

##### **Materials**

- Multilayer Aluminium/ Glass cloth/ PET liner with special adhesive
- Structure: Surface printing/ Aluminium foil/ coated layer/ glass fiber layer/ silicon coated layer/ clear PET liner

Material Component	Top side	Glue	Liner
Spray Stop standard	Al-Glass Fiber HD108	KR3700	PET Coated FB50L
Spray Stop 50 Plus	Al-Glass Fiber HD7628	KR3700	PET Coated FB50L

*When other choices of materials are used per manufacturer's recommendations, the BV agreement is to be obtained.*

### **2. DOCUMENTS AND DRAWINGS**

- Manufacturer's specification sheet dated 20/04/2005
- Letter for T-ISS, declaration KNW dated July 2012
- Installation and application manual of spray stop tape as provided on 06/01/2015
- Product description of spray stop tape 50 Plus for high pressure as provided on 06/01/2015

*No departure from the above documents shall be made without the prior consent of the Society. The manufacturer must inform the Society of any modification or changes to these documents and drawings.*

### **3. TEST REPORTS**

- Tests carried out: Adhesive test, shelf life, tensile strength, pressure test per the test reports N° UTCK 050413-1 dated 15/04/2005 from UTC Laboratory (Korea) and N° 2911/07/2005 dated 30/11/2005 from Gameva bv
- **SPRAYSTOP Standard:** Surface flammability tests according to IMO Res. A.653(16) Annex 1, Part 5 per the test report N° 20050289 dated 21/06/2005 issued by the Fire Insurers Laboratories of Korea (Korea)
- **SPRAYSTOP 50 Plus:** Testing of the surface flammability to certificate a low flame-spread characteristic according to IMO resolution MSC.307(88) - (2010 FTP Code) Annex 1, Part 5 per the test report N° 20150285 dated 03/03/2015 by MPA Dresden GmbH Laboratory in Freiberg (Germany)
- Adhesive strength and tensile strength. test report N° KWQAP20130215BTISS dated 15/02/2013
- Adhesive strength and tensile strength. test report N° KWQAP20130215ATISS dated 15/02/2013
- Puncture impact report test N° T2012-303590-004 dated 11/12/2012

### **4. APPLICATION / LIMITATION**

4.1 - The SPRAYSTOP Standard and SPRAYSTOP 50 Plus anti-splash tapes may be used for screening in systems for fuel oil, lube oil and other flammable oils with pipe flanges and joints complying with the SOLAS 74 as amended, Regulation II-2/4.2.2.5.3; II-2/4.2.3; II-2/4.2.4.

4.2 - The approval is restricted to piping systems which are readily accessible for maintenance and inspection purposes.

4.3 - The SPRAYSTOP Standard and SPRAYSTOP 50 Plus anti-splash tapes cannot be used for pipes insulation or as replacement for pipe gaskets and sealings.

4.4 - The product is to be fitted according to the manufacturer's instructions and satisfactorily checked by the Bureau Veritas's Surveyor for each application on board ship.

#### **5. PRODUCTION SURVEY REQUIREMENTS**

5.1 - The products are to be supplied by **T-ISS B.V.** in compliance with the type described in this certificate.

5.2 - This type of product is within the category HBV of Bureau Veritas Rule Note NR320 and as such does not require a BV product certificate.

5.3 - **T-ISS B.V.** has to make the necessary arrangements to have its works recognised by Bureau Veritas in compliance with the requirements of NR320 for HBV products.

5.4 - For information, **T-ISS B.V.** has declared to Bureau Veritas the following production site:

**T-ISS B.V. Safety Services**  
**Helmkamp 32-34**  
**7091 HR Dinxperlo**  
**THE NETHERLANDS**

#### **6. MARKING OF PRODUCT**

The product shall be marked with at least:

- Manufacturer name or logo
- Format
- Fire-technical rating

#### **7. OTHERS**

It is **T-ISS B.V.**'s responsibility to inform shipbuilders or their sub-contractors of the proper methods of fitting, use and general maintenance of the approved equipment and the conditions of this approval.

*This certificate supersedes the Type Approval Certificate No. 23131/C0 BV issued by the Society.*

**\*\*\* END OF CERTIFICATE \*\*\***