

## Inflation Pumps, Cylinders & Accessories

SKU - 40021154

Scoprega GE900 AA+ 230V – Electric Pump



### Description:

The Scoprega GE900 AA+ 230V Electric Inflator/Deflator is designed for fast inflation and deflation of a wide range of inflatables. It delivers a maximum pressure of 250 mbar with a flow rate of 1700 l/min, making it suitable for applications where quick setup is essential.

With a noise level of max 85 dB, the pump comes with a 25 mm, 1.5 m hose and adaptor fittings for the most common inflation valves. A shoulder strap allows easy transport, making it well-suited for use with rapid deployment emergency shelters, tents, and other large portable inflatable structures.

### KEY FEATURES

- **Maximum Pressure:** 250 mbar: ensures reliable inflation across a wide range of inflatables
- **High Flow Rate:** 1700 l/min: allows rapid setup and deflation when time is critical
- **Noise Level:** max 85 dB: reduced sound output for more comfortable operation
- **Hose Included:** 25 mm, 1.5 m: suitable length and diameter for efficient airflow
- **Adaptor Fittings:** compatible with common inflation valves: versatile use across multiple products
- **Shoulder Strap:** easy to carry and transport: ideal for field and deployment situations
- **Inflation & Deflation Modes:** two modes - supporting quick setup and pack-down of shelters and large inflatables



## Inflation Pumps, Cylinders & Accessories

SKU - 40021154

Scoprega GE900 AA+ 230V – Electric Pump

### SPECIFICATION

- **High Airflow – 1700 l/min:** delivers rapid inflation and deflation to save setup and pack-down time
- **Maximum Pressure – 250 mbar (3.6 psi):** provides reliable performance across small and large inflatables
- **230V Operation:** powerful mains supply for consistent output in the field
- **Low Noise – under 85 dB:** quieter running for more comfortable use in confined or populated areas
- **Practical Hose & Adaptors:** 25 mm, 1.5 m hose with fittings to suit common valve types
- **Easy to Carry:** lightweight 2.4 kg unit with shoulder strap for quick transport between sites
- **Compact Build – 23 x 17 x 2 cm:** saves space and packs neatly with deployment equipment
- **Versatile Applications:** ideal for tents, kayaks, boats, inflatable structures, and rapid deployment shelters

### TECHNICAL INFORMATION

- Air Flow: 1700 l/min
- Max. pressure: 250 mbar (3.6 psi)
- Voltage: 230 Vac
- Max. Current: 4 A
- Functions: Inflate/Deflate
- Dimensions: 23x 17 x 2 cm
- Weight: 2,4 kg
- Noise level: <85 dB