

General Marine Equipment

SKU - 40020501

Hatch Cover Blueliner Tape



Hatch covers of cargo vessels can suffer from leakage during extreme weather conditions, which can result in damage to the goods being transported. To prevent this, Hatch Cover Blueliner Tape offers a highly effective solution that keeps moisture out and creates a tight, weather and smoke-resistant seal. The tape boasts exceptional strength, strong adhesion, and excellent flexibility, with a distinctive blue top layer made of modified PE material that provides optimal protection in extreme situations.

KEY FEATURES

- Hatch Cover Blueliner Tape is tested under practical environments and extreme weather conditions for reliable performance
- The tape can be installed in temperatures ranging from 5 °C to 40 °C
- It can withstand temperatures as low as -15 °C and as high as 70 °C
- Each roll contains 20 meters of self-adhesive SBS bitumen rubber compound
- The tape is coated with a modified blue PE liner and a release PE liner for added convenience
- Hatch Cover Blueliner Tape ensures a tight seal for your cargo during transport in mild or severe weather conditions



General Marine Equipment

SKU - 40020501

Hatch Cover Blueliner Tape

SPECIFICATION

- Hatch Cover Blueliner Tape is designed for reliable performance and tested under practical environments and extreme weather conditions.
- The tape can be easily installed in a temperature range of 5 °C to 40 °C.
- With its ability to withstand temperatures as low as -15 °C and as high as 70 °C, Hatch Cover Blueliner Tape offers exceptional durability.
- Each roll of the tape contains 20 meters of self-adhesive SBS bitumen rubber compound, providing excellent adhesion and sealing.
- The tape features a modified blue PE liner and a release PE liner, which make it convenient to use.
- Hatch Cover Blueliner Tape creates a tight seal that protects your cargo during transport, whether you're facing mild or severe weather conditions.
- Hatch Cover Blueliner Tape is a 2mm-thick self-adhesive SBS bitumen rubber compound, coated with a modified blue PE liner and a release PE liner.
- It can withstand temperatures ranging from -15 °C to 40 °C.
- With proper storage, the tape has a shelf life of 5 years.

TECHNICAL INFORMATION

- Characteristic: 20 m / self-adhesive SBS bitumenrubber coated
- Heat resistance: -15 °C up to 40 °C
- Shelf life: 5 years properly stored
- Thickness: 2

2

