### I.C.Brindle & Co Ltd - Technical Data





The Zinc-Coated Deck Davit with Winch is an excellent solution for those seeking a reliable and robust lifting tool. Constructed with high-quality zinccoated steel, this deck davit provides superior strength and durability, with protection against harsh marine environments, such as on-board a vessel, workboat, or dock. With a lifting capacity of 2000lbs, this davit is ideal for a variety of heavy-duty lifting applications, such as lifting equipment onto boats — making it a popular choice for commercial, industrial, and marine use. The included winch features a user-friendly design, with an easy-to-use handle and brake system that ensures smooth and effortless lifting. The winch also includes a safety feature that prevents overloading, ensuring the safety of the operator and the load being lifted. The Zinc-Coated Deck Davit with Winch is easy to install, making it a versatile solution for your lifting needs. It can be mounted on any flat surface, providing the flexibility and convenience required for a range of lifting tasks.

#### **KEY FEATURES**

- High-quality zinc-coated steel construction for superior strength and durability
- Ideal for heavy-duty lifting applications up to 2000lbs, making it perfect for commercial, industrial, and marine use
- User-friendly winch with an easy-to-use handle and brake system for smooth and effortless lifting
- Safety feature that prevents overloading for operator and load safety
- Versatile and easy to install, with the ability to mount on any flat surface
- Hardened gears for smooth and dependable operation
- Durable stainless steel construction for long-lasting use
- Includes 20 ft. of stainless steel cable for added convenience
- Sturdy 16in.L x 17in.W x 14in.H base for stability during lifting operations
- 11:1 gear ratio for efficient lifting capabilities

1

- Lift range from 48 1/2 93 3/5 inches for versatility
- Boom length adjustable from 26 4/5–80 1/5 inches for greater reach and flexibility
- Column diameter of 4 1/2 inches for added stability
- Height from base to pump support of 10 inches for ease of use
- Height from base to top of 41 1/2 inches for added lifting capabilities.









## I.C.Brindle & Co Ltd - Technical Data



# **SPECIFICATION**

- Hardened gears provide smooth, dependable operation
- Durable stainless steel construction
- Includes 20 ft. of stainless steel cable
- Sturdy 16in.L x 17in.W x 14in.H base
- 11:1 gear ratio
- Capacity (lbs.)= 2,000
- Lift Range (in.) 48 1/2 93 3/5
- Column Diameter (in.) 4 1/2
- Height from Base to Pump Support (in.) 10
- Height from Base to Top (in.) 41 1/2

#### **TECHNICAL INFORMATION**

- Material: Zinc-coated steel
- Ship Weight: 354.0 lbs.
- Base Size (in.) 16 x 17 x 14
- Cable Length (ft.) 20
- Boom Length (in.) 26 4/5–80 1/5

2

