






KEY FEATURES

- Lloyds approved composites with UV resistant gelcoats offer long-lasting protection for equipment stored inside
- Impressive IP rating of 56 guarantees maximum durability in even the harshest environments
- Lightweight yet rigid design ensures high level of rigidity for relatively low weight
- Effective EPDM seal around door aperture for added protection
- 316 stainless steel hinges for added security
- Fire hoses held securely in place with a 316 Stainless steel hose pin
- Customisable door hinging (left or right) with rotary graphite nylon handle for fast access even while wearing gloves
- Optional anti-tamper seal for added protection
- Lloyds and ABS approvals for added peace of mind
- Provides excellent protection for equipment stored inside

















SPECIFICATION

- Lloyds approved composites with UV resistant gelcoats
- IP rating of 56, Lloyds and ABS approvals
- Lightweight yet rigid design with effective EPDM seal
- 316 stainless steel hinges and hose pin
- Customizable door hinging with rotary handle
- Optional anti-tamper seal
- Provides excellent equipment protection

TECHNICAL INFORMATION

- Dimensions (mm)
- Height x width x depth: 626 x 680 x 331
- Aperture: 460H x 520W
- Internal depth: 290
- Weight Kg: 9.7Kg
- Colour: Red RAL 3000
- Material: Lloyds approved composites with UV stabilised gelcoat
- Hinges: 316 Stainless steel
- Handle: Rotary graphite nylon with anti-tamper seal &
- Biomaster® anti-microbial additive
- Seal: EPDM





