I.C.Brindle & Co Ltd - Technical Data





The Galvanised Steel Recovery Wire Rope Winch Cable with Fitted Red Painted Swivel Hooks is made from galvanised steel 7x19 wire rope, which provides superior strength and durability, ensuring that it can handle even the toughest towing jobs. The 2 ton red hook is equipped with a self-closing catch and a swivel, which helps to prevent snagging on your towing line. Additionally, the hook has been professionally attached to the steel wire rope with a thimble, further increasing its strength and reliability. These winch cables are all made in-house by a team of skilled riggers, and meet the BS EN 13411 standard, ensuring that you can have complete confidence in the quality and performance of the lifting winch cable.

KEY FEATURES

- Galvanised steel 7x19 wire rope
- Available in 6mm and 8mm diameters
- Red painted swivel hook with self-closing catch
- Professionally attached hook with a thimble
- Made in-house by skilled riggers
- Meets BS EN 13411 standard
- Superior strength and durability
- Can handle tough towing jobs

1

- Swivel hook prevents snagging on towing line
- Self-closing catch for added security
- Professional attachment increases strength and reliability
- Made to meet industry standards for quality and performance



ADE IN



I.C.Brindle & Co Ltd - Technical Data



SPECIFICATION

- Type: Galvanised steel recovery wire rope winch cable
- Diameter options: 6mm and 8mm
- Material: Galvanised steel 7x19 wire rope
- Hook capacity: 2 tons
- Hook colour: Red
- Hook features: Self-closing catch and swivel
- Hook attachment: Professionally attached with a thimble
- Length options: Various lengths available
- Standard: BS EN 13411
- Application: Recovery and towing use
- Certification: Meets industry standards for quality and performance.

TECHNICAL INFORMATION

- Diameter options: 6mm and 8mm
- Material: Galvanised steel 7x19 wire rope
- Hook capacity: 2 tons
- Hook colour: Red
- Hook features: Self-closing catch and swivel
- Hook attachment: Professionally attached with a thimble
- Standard: BS EN 13411
- Application: Recovery and towing use
- Certification: BS EN 13411 standard (meets industry standards for quality and performance)



