

Davits, Winches & Lifting

SKU - 40020552

Stainless Steel Wire Rope Winch Cable, Hook



Stainless Steel Recovery Wire Rope Winch Cable with Fitted Swivel Hook, available in various lengths to suit your requirements. Crafted from A4-AISI 316 marine grade stainless steel, this winch cable is designed to withstand the elements and resist rust and corrosion. The self-closing catch and swivel hook prevent snagging on your towing line, ensuring smooth and easy operation every time. winch cables are professionally attached with a thimble and fused and tapered for easy attachment to your existing winch. And, because they're made in-house by a team of skilled riggers to BS EN 13411 standard, you can trust that they're built to last.

KEY FEATURES

- Made of high-quality galvanized steel
- 7x19 strand configuration for flexibility and strength
- Professionally fitted winch hook for easy use
- Available in different lengths and diameters
- Durable and long-lasting for heavy-duty use
- Can withstand tough conditions
- Smooth and efficient winching thanks to flexibility and strength
- Ideal replacement for broken winch cable
- Suitable for a range of applications, including trailers and winching boats
- Offers a safe and reliable solution for your winching needs.

**MADE IN
BRITAIN**

1

www.icbrindle.com

+44 (0) 1202 657814

info@icbrindle.com

Follow us on :



YouTube

Davits, Winches & Lifting

SKU - 40020552

Stainless Steel Wire Rope Winch Cable, Hook

SPECIFICATION

- winch cables are fused and tapered for easy attachment to winch
- winch cable is designed to withstand the elements and resist rust and corrosion
- self-closing catch and swivel hook
- Rust-resistant and durable
- Suitable for use with boats and jetskis
- High-quality professional standard
- Smooth and easy operation
- made in-house by a team of skilled riggers to BS EN 13411 standard
- Available Lengths: various

TECHNICAL INFORMATION

- Material: A4-AISI 316 marine grade stainless steel
- Hook Type: Self-closing swivel hook with catch
- Certification: BS EN 13411 standard
- Available Lengths: 10m, 15m, 20m
- End Treatment: Fused and tapered for easy attachment to winch
- Finish: Polished