I.C.Brindle & Co Ltd - Technical Data





MADE IN BRITAIN



The Stainless Steel Wire Rope with Fitted Winch Hook is a reliable and durable winching solution, made from AISI 316 stainless steel for exceptional rust and corrosion resistance. Its 7x19 flexible strand design ensures smooth and efficient operation, and it comes in 4mm and 6mm diameters and various lengths. The professionally swaged soft eye and captive winch hook make installation easy, while providing added flexibility and security during operation.

KEY FEATURES

- Made from high-quality AISI 316 stainless steel for exceptional resistance to rust and corrosion
- 7x19 flexible strand design for superior strength and flexibility
- Available in 4mm and 6mm diameters and various lengths
- Professionally swaged soft eye with a captive winch hook for easy installation and added flexibility
- Durable and reliable solution for winching needs
- Long-lasting performance in harsh environments
- Smooth and efficient operation due to the flexible strand design
- Suitable for a wide range of applications, from recreational winching to professional use
- Easy to install with the professionally swaged soft eye and captive winch hook
- Provides added flexibility and versatility in various rigging configurations
- Minimizes the risk of accidents or damage during operation with the captive winch hook
- Ideal replacement for broken winch cables.





I.C.Brindle & Co Ltd - Technical Data



SPECIFICATION

- Length options: various
- End fitting: professionally swaged soft eye with a captive winch hook
- Rust and corrosion resistance for long-lasting performance
- Smooth and efficient operation
- Easy to install and offers added flexibility in rigging configurations
- Suitable for recreational and professional winching needs
- Minimises the risk of accidents or damage during operation with the captive winch hook
- Ideal replacement for broken winch cables.

TECHNICAL INFORMATION

2

- AISI 316 stainless steel
- Strand design: 7x19 flexible strand
- Available diameters: 4mm and 6mm
- Available lengths: 10, 15, 20, 30 meters
- End fitting: professionally swaged soft eye with a captive winch hook
- Diameter options: 4mm or 6mm

