

# Lifebuoys | 24” Lifebuoys

SKU - 40020581

SOLAS Approved 2.5k, 24-inch Lifebuoy



SOLAS & MED compliant 2.5kg 24-inch Orange lifebuoy with retro-reflective tape and grablines is designed to enhance safety and buoyancy in marine environments and is suitable for various commercial and leisure applications where additional flotation and compliance with international standards are necessary.

## KEY FEATURES

- **Size:** The lifebuoy has a diameter of 24" or 62cm, which makes it suitable for various applications.
- **Compliance:** It meets the SOLAS (Safety of Life at Sea) and MED (Marine Equipment Directive) regulations. These standards ensure that the lifebuoy meets the required safety criteria for use on ships, docks, piers, harbours, and marinas.
- **Colour:** The lifebuoy is orange in colour, which is highly visible in marine environments and aids in quick identification and retrieval during emergencies.
- **Retro-reflective tape:** The lifebuoy is equipped with retro-reflective tape. This tape reflects light back to its source, making the lifebuoy more visible in low-light or night-time conditions. It helps rescuers locate the lifebuoy more easily.
- **Grablines:** The lifebuoy is equipped with grablines, which are typically attached to the outer circumference of the lifebuoy. These lines allow individuals in the water to hold on to the lifebuoy securely while awaiting rescue.
- For use in either fresh or salt water.
- Ideal for deployment near rivers, canals and lakes.
- Complies with RNLI guide.

1



# Lifebuoys | 24” Lifebuoys

SKU - 40020581

SOLAS Approved 2.5k, 24-inch Lifebuoy

## SPECIFICATION

- SOLAS & MED approved 24" (62cm), 2.5kg orange [lifebuoy](#)
- Tough, durable polyethylene.
- Has grab lines and class 1 retro reflective bands.
- Designed for use by Local Authorities River and Water Companies in both commercial and leisure activities.
- For use in either fresh or salt water.
- Ideal for deployment near rivers, canals and lakes.
- Complies with RNLI guide.
- PU foam-filled.
- 180 Newtons
- Outside diameter: 620mm
- Internal Diameter: 410mm
- Depth: 125mm
- Weight: 2.5kg

Note: all dimensions are approximate and subject to manufacturing tolerances.

## TECHNICAL INFORMATION

- 180 Newtons
- Outside diameter: 62cm
- Internal diameter: 41cm
- Depth: 125mm
- Weight: 2.5kg

2

