

# Lifebuoy | 24" Lifebuoy

SKU - 40020103

White 2.5k, 24-inch Lifebuoy



White lifebuoy with retro-reflective tape and grablines is designed to enhance safety and buoyancy in marine environments and is suitable for various commercial and leisure applications. Ideally used around Rivers, Lakes, Canals, Swimming Pools and by small commercial vessels, fishing vessels, yachts and other vessels not required to carry 30" SOLAS approved lifebuoy.

## KEY FEATURES

- **Size:** The lifebuoy has a diameter of 24" or 62cm, which makes it suitable for various applications.
- **Colour:** The lifebuoy is white in colour, which is visible in marine environments and can aid in quick identification and retrieval during emergencies.
- **Retro-reflective tape:** The lifebuoy is equipped with retro-reflective tape. This tape reflects light back to its source, making the lifebuoy more visible in low-light or night-time conditions. It helps rescuers locate the lifebuoy more easily.
- **Grablines:** The lifebuoy is equipped with grablines, which are typically attached to the outer circumference of the lifebuoy. These lines allow individuals in the water to be pulled to the rescuer, and for the casualty to hold on to the lifebuoy securely while awaiting rescue.
- Ideal for deployment near rivers, canals and lakes.
- Complies with RNLI guide.
- PU foam-filled for more durability.

1



[www.icbrindle.com](http://www.icbrindle.com)



+44 (0) 1202 657814



[info@icbrindle.com](mailto:info@icbrindle.com)

Follow us on :





## Lifebuoy | 24" Lifebuoy

SKU - 40020103

White 2.5k, 24-inch Lifebuoy

### SPECIFICATION

- 24" (62cm), 2.5kg white [lifebuoy](#)
- Tough, durable polyethylene.
- Has grab lines and class 1 retro reflective bands.
- Designed for use by Local Authorities River and Water Companies in both commercial and leisure activities.
- For use in either fresh or salt water.
- Ideal for deployment near rivers, canals and lakes.
- PU foam-filled.
- 180 Newtons
- Outside diameter: 620mm
- Internal Diameter: 410mm
- Depth: 125mm
- Weight: 2.5kg

Note: all dimensions are approximate and subject to manufacturing tolerances.

### TECHNICAL INFORMATION

- 180 Newtons
- Outside diameter: 62cm
- Internal diameter: 41cm
- Depth: 125mm
- Weight: 2.5kg