



## TYPE APPROVAL CERTIFICATE

For a 406 Megahertz Distress Beacon for use with the Cospas-Sarsat Satellite System

**Certificate Number: 1351**

**Manufacturer:** Jotron AS, Norway  
**Beacon Type(s):** EPIRB Float Free  
**Beacon Models:** Tron 60AIS  
**Test Laboratory:** TÜV SÜD Product Service, United Kingdom  
**Date of Test:** February – September 2021

Details of the beacon features and battery type are provided overleaf.

The Cospas-Sarsat Council hereby certifies that the 406 MHz Distress Beacon Model identified above is compatible with the Cospas-Sarsat System as defined in documents:

C/S T.001 Specification for Cospas-Sarsat 406 MHz Distress Beacon, Issue 4 – Revision 6, May 2020  
C/S T.007 Cospas-Sarsat 406 MHz Distress Beacon Type Approval Standard, Issue 5 – Revision 5, May 2020

Original TAC 1351 issued on: **6 January 2022**  
TAC 1351 amended on **25 March 2022**  
TAC 351 issued on: **6 January 2022**

Steven W. Lett  
Head of Cospas-Sarsat Secretariat

**NOTE, HOWEVER:**

1. This certificate does not authorize the operation or sale of any 406 MHz distress beacon. Such authorization may require type acceptance by national administrations in countries where the beacon will be distributed and may also be subject to national licensing requirements.
2. This certificate is intended only as a formal notification to the above identified manufacturer that the Cospas-Sarsat Council has determined, on the basis of test data of a beacon submitted by the manufacturer, that 406 MHz distress beacons of the type identified herein meet the standards for use with the Cospas-Sarsat System.
3. Although the manufacturer has formally stated that all beacons identified with the above model name(s) will meet the Cospas-Sarsat specification referenced above, this certificate is not a warranty and Cospas-Sarsat hereby expressly disclaims any and all liability arising out of or in connection with the issuance, use or misuse of the certificate.
4. This certificate is subject to revocation by the Cospas-Sarsat Council should the beacon type for which it is issued cease to meet the Cospas-Sarsat specification. A new certificate may be issued after satisfactory corrective action has been taken and correct performance demonstrated in accordance with the Cospas-Sarsat Type Approval Standard.
5. Cospas-Sarsat type approval testing requirements only address the electrical performance of the beacon at 406 MHz. Conformance of the beacon to operational and environmental requirements is the responsibility of national administrations.
6. This certificate authorizes the use of the registered name mark "Cospas-Sarsat" and of registered trademarks for the Programme's logos, for labelling, instruction materials, and marketing of the 406-MHz beacon model identified, but not for other marketing or sales purposes (i.e., not for general uses beyond this specific beacon model).

<b>Beacon Models:</b>	Tron 60AIS
<b>Manufacturer:</b>	Jotron AS, Norway
<b>Operating temperature range:</b>	-20°C to +55°C (Class 2)
<b>Battery Details:</b>	Lithium/Iron Disulfide (LiFeS <sub>2</sub> ), Energizer, type L91, 8 x AA-size cells
<b>Operating Lifetime:</b>	48 hours
<b>Transmit Frequency:</b>	406.031 MHz

**Beacon Model Features:**

- 121.5 MHz auxiliary radio locating device (power: 17 ±3 dBm, duty cycle: 50%);
- Strobe light (brightness: > 0.75 cd, duty cycle: 21 flashes/minute);
- Internal GPS receiver, manufacturer: Fastrax, model: uBlox, model MAX-M8Q;
- GNSS update rate: 5 minutes;
- Format of operational messages: long;
- Self-test mode, one burst of 520 ms;
- GNSS self-test, one burst of 520 ms;
- Integral antenna;
- Automatic (via water contacts) and manual beacon activation;
- Beacons were tested in EPIRB configuration (“floating in water”, “on deck” and “above ground”); and
- Galileo Return Link Service.

**Approved Beacon Message Protocols:** Beacon is approved for encoding with the message protocols indicated with "Yes" and black text below:

<b>USER PROTOCOLS</b>	<b>USER-LOCATION PROTOCOLS</b>	<b>LOCATION PROTOCOLS</b>
No Maritime with MMSI	No Maritime with MMSI	No Standard Location: EPIRB with MMSI
No Maritime with Radio Call Sign	No Maritime with Radio Call Sign	No Standard Location: EPIRB with Serial Number
No EPIRB Float Free with Serial Number	No EPIRB Float Free with Serial Number	No Standard Location: ELT with 24-bit Address
No EPIRB Non Float Free with Serial Number	No EPIRB Non Float Free with Serial Number	No Standard Location: ELT with Aircraft Operator Designator
No Radio Call Sign	No Radio Call Sign	No Standard Location: ELT with Serial Number
No Aviation	No Aviation	No Standard Location: PLB with Serial Number
No ELT with Serial Number	No ELT with Serial Number	No National Location: EPIRB
No ELT with Aircraft Operator and Serial Number	No ELT with Aircraft Operator and Serial Number	No National Location: ELT
No ELT with Aircraft 24-bit Address	No ELT with Aircraft 24-bit Address	No National Location: PLB
No PLB with Serial Number	No PLB with Serial Number	<b>Yes RLS Location: EPIRB</b>
No National (Short Format Message)		No RLS Location: ELT
No National (Long Format Message)		No RLS Location: PLB
		<b>Yes RLS Location: MMSI</b>
		No ELT(DT) Location: ELT with Serial Number
		No ELT(DT) Location: ELT with Aircraft Operator and Serial Number
		No ELT(DT) Location: ELT with Aircraft 24-bit Address