I.C.Brindle & Co Ltd - Technical Data



DESCRIPTION

JB02R BA SCBA storage cabinet, engineered for applications across onshore and offshore settings. Trusted globally by leading energy firms for its ruggedness, this cabinet is purpose-built to securely accommodate one 30-60 minute self-contained breathing apparatus (SCBA) along with a spare bottle.

KEY FEATURES

- Versatile Application: Suitable for both onshore and offshore environments.
- **Trusted Durability:** Trusted by leading energy companies globally for its ruggedness and reliability.
- **Secure Storage:** Designed to securely house one 30-60 minute SCBA and one spare bottle.
- **High-Quality Materials:** Crafted with Lloyds-approved composites and UV-resistant gelcoats for long-lasting protection.
- **Top-Notch Quality Assurance:** Boasts an IP rating of 56 and approvals from Lloyds and ABS, ensuring top-notch quality.
- **Optimised Design:** Prioritises rigidity while maintaining a lightweight construction.
- Effective Seal: Features an EPDM seal for enhanced protection against external elements.
- **Durable Hardware:** Equipped with 316 stainless steel hinges for lasting performance.
- **Quick Access:** Includes a graphite nylon/stainless steel rotary handle for swift access, even in emergencies.
- Adjustable Door Hinging: Offers flexibility with left or right hinging options.
- convenient Features: Fitted with a sprung clip for the SCBA and a quick-release nylon strap for the spare bottle, enhancing ease of use and readiness.







1



I.C.Brindle & Co Ltd - Technical Data



SPECIFICATION

Standard Specification:

- Dimensions: mm (inches)
- Height x width x depth: 937 x 835 x 347 (36.89 x 32.87 x 13.66")
- Aperture: 755H x 630W (29.72 x 24.8")
- Internal depth: 275 (10.83")
- Weight Kg: 15Kg (33lb)
- Made in UK

Material Specification:

- Colour: Green RAL 6029
- Material: Lloyds approved composites with UV stabilised gelcoat
- Hinges: 316 Stainless steel
- Handle: Nylon / 316 Stainless steel with Biomaster [®] antimicrobial technology and anti-tamper seal facility
- Seal: EPDM

Optional Extras:

- Other RAL colours
- Class 1 fire retardant composites
- Perspex window
- Heating and insulation

TECHNICAL INFORMATION

2

- Colour: Green RAL 6029
- Hinges: 316 Stainless steel
- Weight Kg: 15Kg (33lb)
- Made in the UK

www.icbrindle.com

