

DESCRIPTION


JB83BA Self Contained Breathing Apparatus (SCBA) storage cabinet, designed for extreme environments onshore and offshore. Trusted by top energy companies for durability, it securely houses one 30-60 minute SCBA.

KEY FEATURES

- Extreme Environment Suitability: Designed for use in extreme environments both onshore and offshore, ensuring reliability in challenging conditions.
- Trusted Durability: Trusted by top energy companies for its durability, ensuring long-term usage without compromise.
- **Secure Storage:** Securely houses one 30-60 minute SCBA, providing peace of mind regarding equipment safety.
- Superior Protection: Crafted with Lloyds-approved composites and UV-resistant gelcoats, offering long-lasting protection for stored equipment.
- **Top-notch Quality Assurance:** Boasts an IP rating of 56 and approvals from Lloyds and ABS, ensuring high-quality performance.
- Robust Yet Lightweight Design: Features a rigid design with lightweight materials, combining durability with ease of handling and installation.
- **Effective Sealing:** Utilises an EPDM seal around the door aperture, enhancing protection against environmental elements.
- **Durable Hardware:** Equipped with 316 stainless steel hinges, ensuring lasting performance and reliability.
- Flexible Door Configuration: Door can be left or right-hinged, providing versatility to suit various installation requirements.
- **Quick-Access Handle:** Features a nylon rotary handle for fast access, even with gloves on, ensuring readiness in emergency situations.
- secure Equipment Retention: SCBA is held securely in place by a plastic-coated sprung clip, preventing displacement during storage.

















SPECIFICATION

Standard Specification:

Dimensions: mm (inches)

• Height x width x depth: 816 x 548 x 344

 Aperture: 662H x 395W Internal depth: 275 (10.83")

Weight Kg: 11.5Kg

Made in UK

Material Specification:

• Colour: Green RAL 6029

• Material: Lloyds approved composites with UV stabilised gelcoat

Hinges: 316 Stainless steel

Handle: Nylon / 316 Stainless steel with Biomaster ® antimicrobial technology and anti-tamper

seal facility Seal: EPDM

Optional Extras:

- Other RAL colours
- Class 1 fire retardant composites
- Perspex window
- Heater for cold climates

TECHNICAL INFORMATION

• Colour: Green RAL 6029

Material: Lloyds approved composites with UV stabilised gelcoat

Hinge: 316 Stainless steel

Handle: Nylon/316 Stainless steel rotary with Biomaster® anti-microbial additive and anti-tamper seal facility

Seal: EPDM















